

Speed Queen

CABINET HARDMOUNT WASHER EXTRACTORS - PREP FOR COIN

	Suggested List in U.S. Dollars				
	SCN020	SCN030	SCN040	SCN060	SCN080
Dry Weight Capacity (lbs. / kg)	20 / 8.16	30 / 13.6	40 / 18	60 / 27	80 / 36.3
Quantum Standard 4 Cycle - 5 Segment Micro control with cycle selector switch. Coin meter <u>NOT</u> included.					
NORMAL SPIN: 2 SPEED, 82g (GX2)	4,144	5,952	7,858	10,795	N/A
NORMAL SPIN: F SPEED, 100g (GXF)	N/A	N/A	N/A	11,215	16,282
Quantum Silver 9 Cycle - 8 Segment, multi level vend, time of day pricing, 30 programmable water levels. Micro Processor with IrDA PC/PDA programmability. Coin meter <u>NOT</u> included.					
NORMAL SPIN: 2 SPEED, 82g (JX2)	4,234	6,042	7,948	10,885	N/A
NORMAL SPIN: F SPEED, 100g (JXF)	4,566	6,374	8,368	11,305	16,332
HIGH SPIN: VARIABLE (V) SPEED, 140g (JXV)	4,716	6,524	8,518	11,455	16,482
Quantum Gold 27 Cycle - 8 Segment multi-level vend, time-of-day pricing, cycle modifier keys, 30 programmable water levels <u>by segment</u> , auto shut down & single coin meter.					
NORMAL SPIN: 2 SPEED, 82g (LX2)	4,354	6,162	8,068	11,005	N/A
HIGH SPIN: VARIABLE SPEED, 140g (LXV)	4,836	6,644	8,638	11,575	16,602
Quantum Gold Network 27 Cycle - 8 Segment multi-level vend, time-of-day pricing, cycle modifier keys, 30 programmable water levels <u>by segment</u> , auto shut down & single coin meter. Network board installed.					
NORMAL SPIN: 2 SPEED, 82g (WX2)	4,514	6,322	8,228	11,165	N/A
HIGH SPIN: VARIABLE SPEED, 140g (WXV)	4,996	6,804	8,798	11,735	16,762

Standard Features: 4 Compartment Dispenser, Inlet & Drain Hose Kit; Stainless Steel Front and Top panels, Installation/Operations and Programming Manuals on CD, Top cover key, Jumper harness for 208 volt installations, Extra Fuses, Wiring Diagram & Schematics.

Approval Options	SCN020	SCN030	SCN040	SCN060	SCN080
International - CE Approval (U) U replaces N in position 3 of the model number. International cycles and graphic on Quantum Silver. Metric plumbing standard.	200	200	200	200	200
International - ETL/ETLc Approval (L) L replaces N in position 3 of the model number. International cycles and graphic on Quantum Silver.	OPT - N/C	OPT - N/C	OPT - N/C	OPT - N/C	OPT - N/C
International - No Agency Approval (Z) Z replaces N in position 3 of the model number. International Cycles and Graphic on Quantum Silver. (Electric Heat with F voltage only)	OPT - N/C	OPT - N/C	NA	NA	NA

VEND/ACTUATION OPTIONS (Must select extra cost option)	SCN020	SCN030	SCN040	SCN060	SCN080
Single Coin Meter Must specify currency & denomination.	80	80	80	80	80
Token Acceptor Diameter: STD 1-118 = .880", STD-118-5 = .990"	120	120	120	120	120
Dual Coin Meter (D) Must specify currency & denomination.	150	150	150	150	150
Electronic Coin Drop (E) Must specify currency & denomination.	263	263	263	263	263
Prep for Card Reader (Y) No Coin Meter, No Coin Vault	N/C	N/C	N/C	N/C	N/C
Prep for Central Pay (L) No Coin Meter, Actuation opening covered by decal, No Coin Vault	N/C	N/C	N/C	N/C	N/C

SEE BELOW SIDE FOR OPTIONAL ADDITIONAL EXTRA COST OPTIONS

Speed Queen

CABINET HARDMOUNT WASHER EXTRACTORS - PREP FOR COIN

HEAT OPTIONS	SCN020	SCN030	SCN040	SCN060	SCN080
Prep for Auxiliary Steam Heating (P) Order auxiliary steam kit from "ALS Genuine Parts".	100	100	100	100	100
Auxiliary Electrical Heating* (E) <small>Not Available with B, Y or X voltage</small>	285	285	415	535	980

OTHER OPTIONS	SCN020	SCN030	SCN040	SCN060	SCN080
Stainless Steel Side Panels	120	160	200	240	STD
Coin Box With Lock and Key	75	75	85	85	85
Non-CE Metric Plumbing <small>Optional for N, L, and Z Approvals.</small>	OPT-N/C	OPT-N/C	OPT-N/C	OPT-N/C	OPT-N/C
Treated Shipping Crate <small>Wood framed, not enclosed</small>	147	162	171	176	212

* Made to order option, check with order desk for lead time.

VOLTAGE OPTIONS - 2 SPEED	SCN020	SCN030	SCN040	SCN060	SCN080
120/60/1/2 (B)	175	N/A	N/A	N/A	N/A
380-415/50/3/4 (C)	OPT - N/C	OPT - N/C	OPT - N/C	OPT - N/C	N/A
440-480/60/3/3 (F) <small>No agency approval on electric heated 020 and 030.</small>	175	175	356	356	N/A
200/50/3/3 (J)	122	122	122	122	N/A
208/220-240/60/3/3 (O) <small>208 Volt applications require Jumper installation provided with unit.</small>	STD	STD	STD	STD	N/A
208/220-240/60/1/2 (Y) <small>208 Volt applications require Jumper installation provided with unit.</small>	175	260	342	N/A	N/A

VOLTAGE OPTIONS - F and V SPEED	SCN020	SCN030	SCN040	SCN060	SCN080
200-208/220-240/50/60/3 (Q) - Electric Heat Only <small>200-208 application require Jumper installation provided with unit.</small>	OPT - N/C	OPT - N/C	OPT - N/C	OPT - N/C	OPT - N/C
380-415/50/60/3 (P) <small>020 and 030 not available with Electric Heat.</small>	400	400	400	514	514
440-480/50/60/3 (N) <small>020 and 030 not available with Electric Heat.</small>	400	400	400	514	514
200-208/220-240/50/60/1/3 (X) <small>200-208 application require Jumper installation provided with unit.</small>	STD	STD	STD	STD	STD

High spin SC80 models are not compatible with elevated steel base frames.

Please Specify When Ordering:

Capacity, Control, Actuation, Speed, Electric Specifications (Voltage, Cycle, Phase), Heat, and any other non standard feature