

Speed Queen

CABINET HARDMOUNT WASHER EXTRACTORS - OPL

Dry Weight Capacity (lbs. / kg)	Suggested List in U.S. Dollars					
	SCN020	SCN030	SCN040	SCN060	SCN080	SCN100
Quantum Standard 4 Cycle - 5 Segment Micro control with cycle selector switch.	20 / 8.16	30 / 13.6	40 / 18	60 / 27	80 / 36.3	100 / 45
NORMAL SPIN: F SPEED, (GNF) 100g	4,356	6,218	8,181	11,206	16,425	19,300
Quantum Gold 30 Cycle - 8 Segment Advanced Micro Processor with IrDA PC/PDA programmability. Advanced audit capability.						
HIGH SPIN: V SPEED, (KNV) 200g for 20-80# 165g for 100#	5,221	7,184	9,217	12,338	17,701	20,610

Standard Features: 4 Compartment Dispenser, Inlet & Drain Hose Kit; Stainless Steel Front and Top panels, Installation/Operations and Programming Manuals on CD, Top Cover Key, Jumper Harness for 208 volt installations, extra fuses, Wiring Diagram & Schematics, 4 Signal Chemical Supply Board.

Approval OPTIONS	SCN020	SCN030	SCN040	SCN060	SCN080	SCN100
CE Approval (U) U replaces N in position 3 of the model number. International cycles on Quantum Gold. Metric plumbing standard.	200	200	200	200	200	200
International - ETL/ETLc Approval (L) L replaces N in position 3 of the model number. International cycles on Quantum Gold.	OPT - N/C	OPT - N/C	OPT - N/C	OPT - N/C	OPT - N/C	OPT - N/C
International - No Agency Approval (Z) Z replaces N in position 3 of the model number. International cycles on Quantum Gold. (Electric Heat with N voltage only)	OPT - N/C	OPT - N/C	N/A	N/A	N/A	N/A

EXTRA COST OPTIONS	SCN020	SCN030	SCN040	SCN060	SCN080	SCN100
Stainless Steel Side Panels	120	160	200	240	STD	STD
Auxiliary Electrical Heating* Not available with B or X voltage.	285	285	415	535	980	980
Prep for Auxiliary Steam Heating* Order auxiliary steam kit from "ALS Genuine Parts".	110	110	110	110	110	110
Auxiliary Direct Steam Heating*	N/A	N/A	585	585	585	585
Non-CE Metric Plumbing Optional for N, L, & Z approvals only.	OPT-NC	OPT-NC	OPT-NC	OPT-NC	OPT-NC	OPT-NC
Treated Shipping Crate Wood framed, not enclosed.	147	162	171	176	212	230

VOLTAGE OPTIONS	SCN020	SCN030	SCN040	SCN060	SCN080	SCN100
120/60/1/2 (B)	175	N/A	N/A	N/A	N/A	N/A
200-208/220-240/50/60/1/3 (X) 200-208 application require jumper installation provided with unit.	STD	STD	STD	STD	STD	STD
200-208/220-240/50/60/3 (Q) 020 - 100 Electric Heat only. 200-208 application require jumper installation provided with unit.	OPT - N/C	OPT - N/C	OPT - N/C	OPT - N/C	OPT - N/C	OPT - N/C
380-415/50/60/3 (P)	400	400	400	514	514	514
440-480/50/60/3 (N) No Agency on Electric Heat 020 and 030.	400	400	400	514	514	514

* Made to order option, check with order desk for lead time.

Note: For voltages above or below listed specification, contact customer service for buck boost recommendation.

METAL BASES & MOUNTING BOLT KITS AVAILABLE THROUGH "ALS GENUINE PARTS".

80-100 models are not compatible with elevated steel base frames.

Please Specify When Ordering

Model, Electric Specifications (Voltage, Cycle, Phase), Decals (English or Icon), Plumbing (U.S. Standard or Metric).